KYNAR FLEX®

TECHNICAL DATA SHEET

KYNAR FLEX® 2850 PC

FLUORINATED COPOLYMER PELLET

KYNAR FLEX® resins are fluorinated thermoplastic copolymers.
KYNAR FLEX® 2850 PC resin powder coating is a semi-crystalline copolymer of vinylidene fluoride and hexafluoropropylene.
It has a special particle size making it ideal for spray applied powder coating on metal substrates for abrasion and corrosion protection.

TYPE

PVDF

MAIN APPLICATIONS

- powder coating - others

DELIVERY FORM

- Pellets

PACKAGING

Available packaging:
- 25 kg / 55 lb rigid container
- 25 kg / 55 lb metal drum

SPECIAL CHARACTERISTICS

- Flame & smoke

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on https://www.arkema.com/global/en/products/product-safety/disclaimer/ which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790
arkema.com

ARKEMA