# Monprene® OM-916240 NAT XRD1 (PRELIMINARY DATA)

## Teknor Apex Company - Thermoplastic Elastomer

Thursday, April 2, 2026

### General Information

**Product Description**

OM-916240 NAT XRD1 is a Thermoplastic Elastomer (TPE) material for injection overmolding applications. It has excellent bonding performance onto PC, ABS and PC/ABS substrates.

| General | | | |
|---|---|---|---|
| Material Status | • Preliminary Data | | |
| Availability | • Africa & Middle East<br>• Asia Pacific | • Europe<br>• Latin America | • North America |
| Uses | • Overmolding | | |
| RoHS Compliance | • RoHS Compliant | | |
| Appearance | • Natural Color | • Silver | |
| Forms | • Pellets | | |
| Processing Method | • Injection Molding | | |

### Properties [1]

| Physical | Nominal Value | Unit | Test Method |
|---|---|---|---|
| Density / Specific Gravity | 0.902 | | ASTM D792 |
| Melt Mass-Flow Rate (MFR) (190°C/2.16 kg) | 30 | g/10 min | ASTM D1238 |
| **Elastomers** | **Nominal Value** | **Unit** | **Test Method** |
| Tensile Strength (Break) | 725 | psi | ASTM D412 |
| Tensile Elongation (Break) | 500 | % | ASTM D412 |
| **Hardness** | **Nominal Value** | **Unit** | **Test Method** |
| Durometer Hardness | | | ASTM D2240 |
| Shore A | 40 | | |
| Shore A, 5 sec | 38 | | |
| **Additional Information** | **Nominal Value** | **Unit** | |
| Adhesion to ABS | | | |
| Adhesion to PC | | | |
| Adhesion to PC/ABS | | | |

### Processing Information

| Injection | Nominal Value | Unit |
|---|---|---|
| Rear Temperature | 280 to 320 | °F |
| Middle Temperature | 360 to 410 | °F |
| Front Temperature | 360 to 446 | °F |
| Nozzle Temperature | 392 to 464 | °F |
| Processing (Melt) Temp | 392 to 464 | °F |
| Mold Temperature | 50 to 104 | °F |

### Notes

[1] Typical properties: these are not to be construed as specifications.

Revision Date: 8/18/2023

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

Copyright © 2026 UL Prospector

# Monprene® OM-916240 NAT XRD1 (PRELIMINARY DATA)

## Teknor Apex Company - Thermoplastic Elastomer


**Teknor Apex Company**
**Corporate Headquarters**

*In U.S. for Vinyls, TPEs, Colorants,*

*Engineered Thermoplastics (Chem Polymer)*
505 Central Avenue
Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000
Fax: 401-725-8095
Toll Free (U.S. only) 800-556-3864

www.teknorapex.com
info@teknorapex.com

**Teknor Apex B.V.**

Brightlands Chemelot Campus Umonderbaan 22
6167 RD Geleen, Netherlands

Phone: +31 46 7020 950
Fax: +31 46 7020 990

www.teknorapex.com
tpe@teknorapex.com

**Teknor Apex (Suzhou) Advanced Polymer Compounds Co. Pte. Ltd.**

No. 78 Ping Sheng Road

Suzhou Industrial Park
Jiangsu, China 215126

Phone: (86) 512-6287-1550
Fax: (86) 512-6288-8371

www.teknorapex.com
infotaap@teknoapex.com

**Teknor Apex Asia Pacific PTE. LTD.**

41 Shipyard Road

Singapore 628134

Phone: (65) 6265-2544
Fax: (65) 6265-1821

www.teknorapex.com
infotaap@teknorapex.com



Revision Date: 8/18/2023



The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

Copyright © 2026 UL Prospector