# GLS AC4-628 Blue

## Thermoplastic Elastomer

### Key Characteristics

| Product Description | | |
|---|---|---|
| GLS AC4-628 Blue is a customized grade for gasket application And the compound is formulated based on hydrogenated styrenic block copolymers(SEBS). | | |
| **General** | | |
| Material Status | • Commercial: Active | |
| Regional Availability | • Asia Pacific | |
| Agency Ratings | • EU 10/2011 | • FDA 21 CFR 177.1210 [1] |
| RoHS Compliance | • RoHS Compliant | |
| Appearance | • Blue | |
| Forms | • Pellets | |
| Processing Method | • Injection Molding | |

### Technical Properties [2]

| Physical | Typical Value (English) | Typical Value (SI) | Test Method |
|---|---|---|---|
| Density / Specific Gravity | 0.990 | 0.990 | ASTM D792 |
| **Elastomers** | **Typical Value (English)** | **Typical Value (SI)** | **Test Method** |
| Tensile Strength [3, 4] (Yield, 73°F (23°C)) | 1600 psi | 11.0 MPa | ASTM D412 |
| Tensile Elongation [3, 4] (Break, 73°F (23°C)) | 680 % | 680 % | ASTM D412 |
| **Hardness** | **Typical Value (English)** | **Typical Value (SI)** | **Test Method** |
| Durometer Hardness (Shore A, 10 sec) | 84 | 84 | ASTM D2240 |
| **Fill Analysis** | **Typical Value (English)** | **Typical Value (SI)** | **Test Method** |
| Apparent Viscosity | | | ASTM D3835 |
| 392°F (200°C), 11200 sec^-1 | 10.6 Pa·s | 10.6 Pa·s | |

### Processing Information

| Injection | Typical Value (English) | Typical Value (SI) |
|---|---|---|
| Suggested Max Regrind | 20 % | 20 % |
| Rear Temperature | 330 to 370 °F | 166 to 188 °C |
| Middle Temperature | 350 to 380 °F | 177 to 193 °C |
| Front Temperature | 370 to 440 °F | 188 to 227 °C |
| Nozzle Temperature | 360 to 420 °F | 182 to 216 °C |
| Processing (Melt) Temp | 380 to 440 °F | 193 to 227 °C |
| Mold Temperature | 60 to 100 °F | 16 to 38 °C |

**Injection Notes**

Purge thoroughly before and after use of this product with a low flow (0.5 - 2.5 MFR) polyethylene (PE) or polypropylene (PP).

The GLS AC4-628 Blue has excellent melt stability. Maximum residence times may vary, depending on the size of the barrel. Generally, the barrel should be emptied if it is idle for periods of 8 - 10 minutes or longer.

Drying is not Required

Copyright ©, 2026 Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as “typical” or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. Avient makes no warranties or guarantees respecting suitability of either Avient’s products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. Avient MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

### Notes

[1] Contact GLS Thermoplastic Elastomers for a copy of the FDA Compliance letter

[2] Typical values are not to be construed as specifications.

[3] Die C

[4] 2 hr

### CONTACT INFORMATION

**North America**
Avon Lake, United States
33587 Walker Road
Avon Lake, OH, United States , 44012
+1 440 930 1000
+1 844 4AVIENT

**South America**
Sao Paulo, Brazil
Av. Francisco Nakasato, 1700
13295-000 Itupeva
Sao Paulo, Brazil
+55 11 4593 9200

**Asia**
Shanghai, China
2F, Block C
200 Jinsu Road
Pudong, 201206
Shanghai, China
+86 (0) 21 6028 4888

**Europe**
Pommerloch, Luxembourg
19 Route de Bastogne
Pommerloch, Luxembourg , L-9638
+352 269 050 35

avient.com

Copyright ©, 2026 Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as “typical” or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. Avient makes no warranties or guarantees respecting suitability of either Avient’s products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. Avient MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.